





Belt conveyors

MGF 300 to MGF 2000

Technical data

Design:	horizontal/inclined/concave/convex/reversible/movable
Materials:	S235JR (St37) / 1.4301 / vz
Types of gear:	spur gears, flat gears and bevel gears
Types of drive:	direct drive and coupling drive
Safety components:	rotation speed monitoring / pull-rope emergency stop switch / off-track switch / safety guard
Accessories:	stable, tilted plate design / lower belt cover / plough scraper of diagonal scraper / centring stations /
	guidance stations / lateral rollers
Material guidance:	with product guide rails and slat curtains
Shaft seals:	seal insert
Tensioning station:	spindle tensioning unit / weight-loaded rear tensioning point with tensioning carriage /
	weight-loaded central tensioning point
Drive station:	wiper system / cleaning brushes
Belt qualities:	certified food-safe / heat and cold resistant / oil and grease resistant / with different liners /
	steel cord belts
Additional options:	ATEX / discharge trolleys / belt scales / overbelt magnet / dust extraction nozzles / cover hoods
	(Organit, 1.4301, aluminium, vz) / special materials / special coating / fully enclosed /
	filling level indicator / movable

Trough belt conveyors MGF from AMF-Bruns

Delicate goods transported gently over long distances



The benefits of AMF-Bruns belt conveyors:

- volume flows of up to 2,200 m³/h
- suitable for very long horizontal conveying distances
- low energy and space requirements
- low maintenance

 protects the transported goods



Please feel free to contact us.





